
NO. DATE BY NO. DATE BY NO. DATE BY


5-07 MSM



ARE FOR 11" X 17"

PRINTS ONLY

CADD FILE NAME e6g\_0507.std DRWG. ORIG. DATE: DECEMBER, 2004



## NOTES

GRATE DETAILS

(SEE NOTE NO. 9)

- 1. INLET MEDIAN DRAIN MAY BE EITHER PRECAST OR CAST-IN-PLACE. PRECAST UNITS SHALL MEET THE REQUIREMENTS OF ASTM C478. PRIOR APPROVAL OF THE SHOP DRAWING WILL BE REQUIRED ON PRECAST UNITS.
- 2. A 1" SIDE DRAFT IS ALLOWED FOR FORM REMOVAL.
- 3. CAST-IN-PLACE INLET MEDIAN DRAINS SHALL CONFORM TO SECTION 609 - MINOR STRUCTURES OF THE CURRENT ITD STANDARD SPECIFICATIONS FOR HIGHWAY CONSTRUCTION.
- 4. THE GRADE LINE OF THE TOP INSIDE OF ANY PIPE SHALL ENTER AT A POINT NO LOWER THAN THE TOP INSIDE OF THE OUTLET PIPE.
- 5. PIPES CAN ENTER OR LEAVE THE BOX IN ANY DIRECTION. ALL CONNEC-TIONS AND BROKEN AREAS SHALL BE GROUTED SMOOTH.
- 6. STEEL ANGLES SHALL BE SET SO THAT EACH BEARING BAR OF PREFAB-RICATED GRATE SHALL HAVE FULL BEARING ON BOTH ENDS. THE FINISHED TOP OF CONCRETE SHALL BE EVEN WITH THE ANGLE/GRATE SURFACE. THE STRUCTURAL STEEL NEED NOT BE PAINTED BUT SHALL MEET THE REQUIRE-MENTS OF ASTM A36.
- 7. ALL METAL REINFORCEMENT SHALL BE NO. 4 BARS. METAL REINFORCE-MENT SHALL BE SMOOTH CUT TO FIT AROUND PIPES. VERTICAL BARS NEED TO LENGTHENED TO ACCOMMODATE INLET DEPTH.
- 8. THE (10) FLAT BARS AT THE 45° ANGLE MUST BE POINTED DOWN AND IN THE DIRECTION OF THE FLOW.
- 9. GRAY IRON CAST TO THE DIMENSIONS GIVEN FOR THE STEEL GRATES MAY BE USED. THE CASTINGS SHALL CONFORM TO AASHTO M306 CLASS 35B GRAY IRON CASTINGS.

10. NOT TO SCALE.

\_\_\_FLOW

(SEE NOTE NO. 8)

SECTION Y-Y

STANDARD DRAWING

English STANDARD DRWG. NO. E-6-G SHEET 1 OF

x 11/8" x 2'-43/4" FLAT BAR

SECTION X-X

**IDAHO** TRANSPORTATION DEPARTMENT

(DEVED PMENT) CHIEF ENGINEER

INLET MEDIAN DRAIN TYPE 9

BOISE IDAHO